

---

## 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

---

### 1.1 Product identifier

**Product name** WHITE CREAM HARDENER CARTON 4OZ / 100 PER CASE  
**Synonyms** WHITE CREAM HDNR. CTN 4OZ / 100 PER CASE

### 1.2 Uses and uses advised against

**Uses** INDUSTRIAL PAINT

### 1.3 Details of the supplier of the product

**Supplier name** CDK STONE PTY LTD  
**Address** 4 - 6 Freighter Rd, Moorabbin, VIC, 3189, AUSTRALIA  
**Telephone** (03) 8552 6000  
**Fax** (03) 8552 6001  
**Email** [help@cdkstone.com.au](mailto:help@cdkstone.com.au)  
**Website** <http://www.cdkstone.com.au>

### 1.4 Emergency telephone numbers

**Emergency** 13 11 26

---

## 2. HAZARDS IDENTIFICATION

---

### 2.1 Classification of the substance or mixture

CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

#### Physical Hazards

Organic Peroxides: Type E and F

#### Health Hazards

Skin Sensitisation: Category 1  
Serious Eye Damage / Eye Irritation: Category 2A

#### Environmental Hazards

Aquatic Toxicity (Acute): Category 1  
Aquatic Toxicity (Chronic): Category 1

### 2.2 GHS Label elements

**Signal word** WARNING

#### Pictograms



#### Hazard statements

H242 Heating may cause a fire.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.

## PRODUCT NAME WHITE CREAM HARDENER CARTON 4OZ / 100 PER CASE

### Prevention statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P234	Keep only in original packaging.
P240	Ground and bond container and receiving equipment.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

### Response statements

P302 + P352	IF ON SKIN: Wash with plenty of water.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P321	Specific treatment is advised - see first aid instructions.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P370 + P378	In case of fire: Use appropriate media to extinguish.
P391	Collect spillage.

### Storage statements

P410	Protect from sunlight.
P411	Store at temperatures not exceeding that specified on the SDS/label.
P420	Store separately.

### Disposal statements

P501	Dispose of contents/container in accordance with relevant regulations.
------	--

### 2.3 Other hazards

No information provided.

## 3. COMPOSITION/ INFORMATION ON INGREDIENTS

### 3.1 Substances / Mixtures

Ingredient	CAS Number	EC Number	Content
BENZOYL PEROXIDE	94-36-0	202-327-6	25 to 50%
NON HAZARDOUS INGREDIENTS	Not Available	Not Available	Remainder
C9-11 BRANCHED ALKYL BENZOATE	131298-44-7	603-470-0	10 to 25%

## 4. FIRST AID MEASURES

### 4.1 Description of first aid measures

<b>Eye</b>	If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.
<b>Inhalation</b>	If inhaled, remove from contaminated area. To protect rescuer, use a Type A (Organic vapour) respirator or an Air-line respirator (in poorly ventilated areas). Apply artificial respiration if not breathing.
<b>Skin</b>	If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.
<b>Ingestion</b>	For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor (at once).
<b>First aid facilities</b>	Eye wash facilities and safety shower should be available.

### 4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

### 4.3 Immediate medical attention and special treatment needed

Treat symptomatically.

## 5. FIRE FIGHTING MEASURES

### 5.1 Extinguishing media

Dry agent, carbon dioxide, foam or water fog. Prevent contamination of drains or waterways. Do not use water jets.

**5.2 Special hazards arising from the substance or mixture**

Combustible. May evolve toxic gases (benzoic acid, carbon oxides, benzene, biphenyls, phenyl benzoate and terphenyls) when heated to decomposition. Burns fiercely. Do not heat as this product may explode.

**5.3 Advice for firefighters**

Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

**5.4 Hazchem code**

1W

1 Coarse Water Spray.

W Risk of violent reaction or explosion. Wear liquid-tight chemical protective clothing and breathing apparatus. Contain spill and run-off.

---

**6. ACCIDENTAL RELEASE MEASURES**

---

**6.1 Personal precautions, protective equipment and emergency procedures**

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS. Clear area of all unprotected personnel. Ventilate area where possible. Contact emergency services where appropriate.

**6.2 Environmental precautions**

Prevent product from entering drains and waterways.

**6.3 Methods of cleaning up**

Contain spillage, then cover / absorb spill with non-combustible absorbent material (vermiculite, sand, or similar), collect and place in suitable containers for disposal. Eliminate all sources of ignition.

**6.4 Reference to other sections**

See Sections 8 and 13 for exposure controls and disposal.

---

**7. HANDLING AND STORAGE**

---

**7.1 Precautions for safe handling**

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

**7.2 Conditions for safe storage, including any incompatibilities**

Store in a cool, dry, well ventilated area, removed from incompatible substances, heat or ignition sources and foodstuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use. Check regularly for leaks or spills. Large storage areas should have appropriate ventilation and fire protection systems.

**7.3 Specific end uses**

No information provided.

---

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

---

**8.1 Control parameters****Exposure standards**

Ingredient	Reference	TWA		STEL	
		ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
Benzoyl peroxide	SWA [AUS]	--	5	--	--

**Biological limits**

No biological limit values have been entered for this product.

**8.2 Exposure controls**

**Engineering controls** Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical explosion proof extraction ventilation is recommended.

## PRODUCT NAME WHITE CREAM HARDENER CARTON 4OZ / 100 PER CASE

### PPE

<b>Eye / Face</b>	Wear splash-proof goggles.
<b>Hands</b>	Wear barrier gloves.
<b>Body</b>	Wear coveralls. If spraying, with prolonged use, or if in confined areas, wear impervious coveralls.
<b>Respiratory</b>	Wear a Type A (Organic vapour) respirator. If sanding dry product, wear a Class P1 (Particulate) respirator. If spraying, with prolonged use, or if in confined areas, wear an Air-line respirator.



---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

### 9.1 Information on basic physical and chemical properties

<b>Appearance</b>	PASTE
<b>Odour</b>	SLIGHT ODOUR
<b>Flammability</b>	COMBUSTIBLE
<b>Flash point</b>	94°C
<b>Boiling point</b>	NOT AVAILABLE
<b>Melting point</b>	NOT AVAILABLE
<b>Evaporation rate</b>	NOT AVAILABLE
<b>pH</b>	NOT AVAILABLE
<b>Vapour density</b>	NOT AVAILABLE
<b>Relative density</b>	1.2
<b>Solubility (water)</b>	NOT AVAILABLE
<b>Vapour pressure</b>	NOT AVAILABLE
<b>Upper explosion limit</b>	NOT AVAILABLE
<b>Lower explosion limit</b>	NOT AVAILABLE
<b>Partition coefficient</b>	NOT AVAILABLE
<b>Autoignition temperature</b>	NOT AVAILABLE
<b>Decomposition temperature</b>	NOT AVAILABLE
<b>Viscosity</b>	NOT AVAILABLE
<b>Explosive properties</b>	NOT AVAILABLE
<b>Oxidising properties</b>	NOT AVAILABLE
<b>Odour threshold</b>	NOT AVAILABLE

---

## 10. STABILITY AND REACTIVITY

---

### 10.1 Reactivity

Carefully review all information provided in sections 10.2 to 10.6.

### 10.2 Chemical stability

Stable under recommended conditions of storage.

### 10.3 Possibility of hazardous reactions

Hazardous polymerisation is not expected to occur.

### 10.4 Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources.

### 10.5 Incompatible materials

Incompatible (may cause fires/ explosions) with heat, alcohols, metallic naphthenates, acids (e.g. nitric acid), alkalis (e.g. sodium hydroxide), amines, nitrates, methacrylates, combustible material, oxidising agents (e.g. hypochlorites) and reducing agents (e.g. sulphites).

### 10.6 Hazardous decomposition products

May evolve toxic gases (benzoic acid, carbon oxides, benzene, biphenyls, phenyl benzoate and terphenyls) when heated to decomposition.

## 11. TOXICOLOGICAL INFORMATION

### 11.1 Information on toxicological effects

**Acute toxicity** Based on available data, the classification criteria are not met.

**Information available for the ingredients:**

Ingredient	Oral LD50	Dermal LD50	Inhalation LC50
BENZOYL PEROXIDE	5700 mg/kg (mouse)	> 1000 mg/kg (mammal)	--

**Skin** Contact may result in irritation, redness, pain and rash.

**Eye** Contact may result in irritation, lacrimation, pain and redness.

**Sensitisation** May cause an allergic skin reaction. This product is not classified as a respiratory sensitiser.

**Mutagenicity** Not classified as a mutagen.

**Carcinogenicity** Benzoyl peroxide is not classifiable as to its carcinogenicity in humans (IARC Group 3).

**Reproductive** Not classified as a reproductive toxin.

**STOT - single exposure** Over exposure may result in irritation of the nose and throat, coughing and headache. Over exposure may result in decreased pulse and temperature, dyspnea and wheezing, abdominal pain, and stupor.

**STOT - repeated exposure** Not classified as causing organ damage from repeated exposure.

**Aspiration** Not classified as causing aspiration.

## 12. ECOLOGICAL INFORMATION

### 12.1 Toxicity

Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects.

### 12.2 Persistence and degradability

No information provided.

### 12.3 Bioaccumulative potential

No information provided.

### 12.4 Mobility in soil

No information provided.

### 12.5 Other adverse effects

No information provided.

## 13. DISPOSAL CONSIDERATIONS

### 13.1 Waste treatment methods

**Waste disposal** Mix components together (small amounts), absorb with sand, vermiculite or similar and dispose of to an approved landfill site. Ensure protective equipment is worn when mixing. Do not seal containers/tins until reaction is complete. Contact the manufacturer/supplier for additional information (if required). Prevent contamination of drains and waterways as environmental damage may result.

**Legislation** Dispose of in accordance with relevant local legislation.

## 14. TRANSPORT INFORMATION

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE



**PRODUCT NAME WHITE CREAM HARDENER CARTON 4OZ / 100 PER CASE**

	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
<b>14.1 UN Number</b>	3108	3108	3108
<b>14.2 Proper Shipping Name</b>	ORGANIC PEROXIDE TYPE E, SOLID	ORGANIC PEROXIDE TYPE E, SOLID	ORGANIC PEROXIDE TYPE E, SOLID
<b>14.3 Transport hazard class</b>	5.2	5.2	5.2
<b>14.4 Packing Group</b>	II	II	II

**14.5 Environmental hazards**

Marine Pollutant.

**14.6 Special precautions for user**

Hazchem code 1W

EmS F-J, S-R

**Other information** The environmentally hazardous substance mark is not required when transported in packages of less than 5 kg/L (UN Model Regulations: Special Provision 375; IATA: Special Provision A197; IMDG: Special Provision 969) or less than 500 kg/L by Australian Road and Rail.

**15. REGULATORY INFORMATION****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

**Poison schedule** Classified as a Schedule 5 (S5) Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

**Classifications** Safe Work Australia criteria is based on the Globally Harmonised System (GHS) of Classification and Labelling of Chemicals (GHS Revision 7).

**Inventory listings** **AUSTRALIA: AIIC (Australian Inventory of Industrial Chemicals)**  
All components are listed on AIIC, or are exempt.  
**EUROPE: EINECS (European Inventory of Existing Chemical Substances)**  
All components are listed on EINECS, or are exempt.  
**UNITED STATES: TSCA (US Toxic Substances Control Act)**  
All components are listed on the TSCA inventory, or are exempt.

**16. OTHER INFORMATION**

**Additional information** ORGANIC PEROXIDES: Fires involving organic peroxides can be intense and move rapidly due to product rapid decomposition with release of oxygen and may involve explosions. If spilt on combustible materials it may spontaneously ignite. A diluent is often added to organic peroxides to reduce shock sensitivity.

SYNERGISM - ANTAGONISM: Ingredients in this product may act together to aggravate or reduce adverse effects. Accordingly the time weighted average concentration (TWA) provided for single ingredients should be considered as a guide only and all due care exercised when handling.

WELDING - SANDING - CUTTING DRIED OR CURED PRODUCT: If sanding, cutting or welding dried or cured product, adverse health effects may be avoided by the use of appropriate engineering controls and/or personal protective equipment. If welding, wear a Class P2 (Metal fume) respirator and depending on the nature of the surface being welded, additional protection (e.g. for organic vapours/acid gas) may also be required. A Class P1 (Particulate) respirator is recommended if dust is generated.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:  
The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as form of product, method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

**HEALTH EFFECTS FROM EXPOSURE:**

It should be noted that the effects from exposure to this product will depend on several factors including: form of product; frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

**Abbreviations**

ACGIH	American Conference of Governmental Industrial Hygienists
CAS #	Chemical Abstract Service number - used to uniquely identify chemical compounds
CNS	Central Nervous System
EC No.	EC No - European Community Number
EMS	Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous Goods)
GHS	Globally Harmonized System
GTEPG	Group Text Emergency Procedure Guide
IARC	International Agency for Research on Cancer
LC50	Lethal Concentration, 50% / Median Lethal Concentration
LD50	Lethal Dose, 50% / Median Lethal Dose
mg/m <sup>3</sup>	Milligrams per Cubic Metre
OEL	Occupational Exposure Limit
pH	relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).
ppm	Parts Per Million
STEL	Short-Term Exposure Limit
STOT-RE	Specific target organ toxicity (repeated exposure)
STOT-SE	Specific target organ toxicity (single exposure)
SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons
SWA	Safe Work Australia
TLV	Threshold Limit Value
TWA	Time Weighted Average

**Report status**

This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

**Prepared by**

Risk Management Technologies  
5 Ventnor Ave, West Perth  
Western Australia 6005  
Phone: +61 8 9322 1711  
Fax: +61 8 9322 1794  
Email: [info@rmt.com.au](mailto:info@rmt.com.au)  
Web: [www.rmtglobal.com](http://www.rmtglobal.com)

**[ End of SDS ]**