

---

## 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

---

### 1.1 Product identifier

**Product name**            **AGER**  
**Synonyms**                **WAXES IN SOLUTION**

### 1.2 Uses and uses advised against

**Uses**                      **PRIMER • STONE CARE**

### 1.3 Details of the supplier of the product

**Supplier name**            **CDK STONE PTY LTD**  
**Address**                  4 - 6 Freighter Rd, Moorabbin, VIC, 3189, AUSTRALIA  
**Telephone**                (03) 8552 6000  
**Fax**                         (03) 8552 6001  
**Email**                      [help@cdkstone.com.au](mailto:help@cdkstone.com.au)  
**Website**                  <http://www.cdkstone.com.au>

### 1.4 Emergency telephone numbers

**Emergency**                13 11 26

---

## 2. HAZARDS IDENTIFICATION

---

### 2.1 Classification of the substance or mixture

CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

#### Physical Hazards

Flammable Liquids: Category 2

#### Health Hazards

Aspiration Hazard: Category 1  
Serious Eye Damage / Eye Irritation: Category 2A  
Specific Target Organ Toxicity (Single Exposure): Category 3 (Narcotic Effects)  
Repeated exposure may cause skin dryness or cracking.

#### Environmental Hazards

Not classified as an Environmental Hazard

### 2.2 GHS Label elements

**Signal word**                **DANGER**

#### Pictograms



#### Hazard statements

AUH066                      Repeated exposure may cause skin dryness or cracking.  
H225                         Highly flammable liquid and vapour.  
H304                         May be fatal if swallowed and enters airways.  
H319                         Causes serious eye irritation.  
H336                         May cause drowsiness or dizziness.

**PRODUCT NAME AGER****Prevention statements**

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

**Response statements**

P301 + P310	IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTRE or doctor/physician if you feel unwell.
P331	Do NOT induce vomiting.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P370 + P378	In case of fire: Use appropriate media to extinguish.

**Storage statements**

P403 + P233 + P235	Store in a well-ventilated place. Keep cool. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

**Disposal statements**

P501	Dispose of contents/container in accordance with relevant regulations.
------	--

**2.3 Other hazards**

No information provided.

---

**3. COMPOSITION/ INFORMATION ON INGREDIENTS**

---

**3.1 Substances / Mixtures**

Ingredient	CAS Number	EC Number	Content
ETHYL ACETATE	141-78-6	205-500-4	20 to 30%
NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (<0.1% W/W BENZENE)	64742-48-9	265-150-3	10 to 20%
N-BUTYL ACETATE	123-86-4	204-658-1	1 to 3.5%
DIOCTYL TIN DILAUATE	3648-18-8	222-883-3	0.25 to <0.3%
METHANOL	67-56-1	200-659-6	0.15 to 0.2%
NON HAZARDOUS INGREDIENTS	Not Available	Not Available	Remainder

---

**4. FIRST AID MEASURES**

---

**4.1 Description of first aid measures**

<b>Eye</b>	If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.
<b>Inhalation</b>	If inhaled, remove from contaminated area. To protect rescuer, use a Type A (Organic vapour) respirator or an Air-line respirator (in poorly ventilated areas). Apply artificial respiration if not breathing.
<b>Skin</b>	If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.
<b>Ingestion</b>	For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed, do not induce vomiting.
<b>First aid facilities</b>	Eye wash facilities and safety shower are recommended.

**4.2 Most important symptoms and effects, both acute and delayed**

See Section 11 for more detailed information on health effects and symptoms.

#### **4.3 Immediate medical attention and special treatment needed**

Treat symptomatically.

---

### **5. FIRE FIGHTING MEASURES**

---

#### **5.1 Extinguishing media**

Dry agent, carbon dioxide or foam. Prevent contamination of drains and waterways.

#### **5.2 Special hazards arising from the substance or mixture**

Highly flammable. May evolve toxic gases (carbon oxides, hydrocarbons) when heated to decomposition. Vapour may form explosive mixtures with air. Eliminate all ignition sources including cigarettes, open flames, spark producing switches/tools, heaters, naked lights, pilot lights, mobile phones, etc when handling. Earth containers when dispensing fluids.

#### **5.3 Advice for firefighters**

Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

#### **5.4 Hazchem code**

- 3YE
- 3 Alcohol Resistant Foam is the preferred firefighting medium but, if it is not available, normal foam can be used.
- Y Risk of violent reaction or explosion. Wear full fire kit and breathing apparatus. Contain spill and run-off.
- E Evacuation of people in and around the immediate vicinity of the incident should be considered.

---

### **6. ACCIDENTAL RELEASE MEASURES**

---

#### **6.1 Personal precautions, protective equipment and emergency procedures**

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS. Clear area of all unprotected personnel. Ventilate area where possible. Contact emergency services where appropriate.

#### **6.2 Environmental precautions**

Prevent product from entering drains and waterways.

#### **6.3 Methods of cleaning up**

Contain spillage, then cover / absorb spill with non-combustible absorbent material (vermiculite, sand, or similar), collect and place in suitable containers for disposal.

#### **6.4 Reference to other sections**

See Sections 8 and 13 for exposure controls and disposal.

---

### **7. HANDLING AND STORAGE**

---

#### **7.1 Precautions for safe handling**

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

#### **7.2 Conditions for safe storage, including any incompatibilities**

Store tightly sealed in a cool, dry, well ventilated area, removed from incompatible substances, heat or ignition sources and foodstuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use. Check regularly for leaks or spills. Large storage areas should be bunded and have appropriate fire protection and ventilation systems.

#### **7.3 Specific end uses**

No information provided.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### 8.1 Control parameters

#### Exposure standards

Ingredient	Reference	TWA		STEL	
		ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
Butyl acetate	SWA [Proposed]	50	270	200	950
Ethyl acetate	SWA [AUS]	200	720	400	1440
Methanol	SWA [AUS]	200	262	250	328
Mineral Oil Mist	SWA [AUS]	--	5	--	--
Mineral spirits	SWA [Proposed]	50	295	100	593
Tin, organic compounds (as Sn)	SWA [AUS]	--	0.1	--	0.2
Tin, organic compounds (as Sn)	SWA [Proposed]	--	0.1	--	--
n-Butyl acetate	SWA [AUS]	150	713	200	950

#### Biological limits

Ingredient	Reference	Determinant	Sampling Time	BEI
METHANOL	ACGIH BEI	Methanol in urine	End of shift	15 mg/L

### 8.2 Exposure controls

**Engineering controls** Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical explosion proof extraction ventilation is recommended. Flammable/explosive vapours may accumulate in poorly ventilated areas. Vapours are heavier than air and may travel some distance to an ignition source and flash back.

#### PPE

- Eye / Face** Wear splash-proof goggles.
- Hands** Wear PVA or barrier gloves.
- Body** When using large quantities or where heavy contamination is likely, wear coveralls.
- Respiratory** Where an inhalation risk exists, wear a Type A (Organic vapour) respirator.



## 9. PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties

<b>Appearance</b>	COLOURLESS LIQUID
<b>Odour</b>	TYPICAL ODOUR
<b>Flammability</b>	HIGHLY FLAMMABLE
<b>Flash point</b>	< 23°C
<b>Boiling point</b>	> 35°C
<b>Melting point</b>	NOT AVAILABLE
<b>Evaporation rate</b>	NOT AVAILABLE
<b>pH</b>	NOT AVAILABLE
<b>Vapour density</b>	NOT AVAILABLE
<b>Relative density</b>	1.10
<b>Solubility (water)</b>	INSOLUBLE
<b>Vapour pressure</b>	NOT AVAILABLE
<b>Upper explosion limit</b>	NOT AVAILABLE
<b>Lower explosion limit</b>	NOT AVAILABLE
<b>Partition coefficient</b>	NOT AVAILABLE
<b>Autoignition temperature</b>	NOT AVAILABLE
<b>Decomposition temperature</b>	NOT AVAILABLE
<b>Viscosity</b>	NOT AVAILABLE
<b>Explosive properties</b>	NOT AVAILABLE
<b>Oxidising properties</b>	NOT AVAILABLE
<b>Odour threshold</b>	NOT AVAILABLE

**9.2 Other information**

VOC

476.92 g/L

**10. STABILITY AND REACTIVITY**

**10.1 Reactivity**

Carefully review all information provided in sections 10.2 to 10.6.

**10.2 Chemical stability**

Stable under recommended conditions of storage.

**10.3 Possibility of hazardous reactions**

Polymerization is not expected to occur.

**10.4 Conditions to avoid**

Avoid shock, friction, heavy impact, heat, sparks, open flames and other ignition sources.

**10.5 Incompatible materials**

Incompatible with oxidising agents (e.g. hypochlorites), acids (e.g. nitric acid), alkalis (e.g. sodium hydroxide), heat and ignition sources. Incompatible with aluminium, zinc and plastic.

**10.6 Hazardous decomposition products**

May evolve toxic gases (carbon oxides, hydrocarbons) when heated to decomposition.

**11. TOXICOLOGICAL INFORMATION**

**11.1 Information on toxicological effects**

**Acute toxicity** May be harmful if swallowed.

**Information available for the ingredients:**

Ingredient	Oral LD50	Dermal LD50	Inhalation LC50
ETHYL ACETATE	4100 mg/kg (mouse)	--	1600 ppm/8hrs (rat)
NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (<0.1% W/W BENZENE)	> 5000 mg/kg (OECD TG 401)	> 2000 mg/kg (OECD TG 402)	> 5610 mg/m <sup>3</sup> (OECD TG 403)
N-BUTYL ACETATE	10760 mg/kg (rat)	14112 mg/kg (rabbit)	> 21 mg/L/4hrs (rat)
DIOCTYL TIN DILAURATE	6450 mg/kg (Rat)	--	--
METHANOL	300 mg/kg (human)	15,800 mg/kg (rabbit)	50 g/m <sup>3</sup> /2 hours (mouse)

**Skin** Contact may result in drying and defatting of the skin, rash and dermatitis.

**Eye** Causes serious eye irritation. Contact may result in irritation, lacrimation, pain and redness.

**Sensitisation** Not classified as causing skin or respiratory sensitisation.

**Mutagenicity** Not classified as a mutagen.

**Carcinogenicity** Not classified as a carcinogen.

**Reproductive** Not classified as a reproductive toxin.

**STOT - single exposure** Over exposure may result in irritation of the nose and throat, coughing and headache. High level exposure may result in nausea, dizziness and drowsiness.

**STOT - repeated exposure** Not classified as causing organ damage from repeated exposure.

**Aspiration** Aspiration into the lungs may result in chemical pneumonitis and pulmonary oedema.

**12. ECOLOGICAL INFORMATION**

**12.1 Toxicity**

No ecological data is available for this product.

**12.2 Persistence and degradability**

Ethyl acetate is considered readily biodegradable.

**PRODUCT NAME AGER****12.3 Bioaccumulative potential**

Ethyl acetate is not considered to be bioaccumulative (Log Kow ≤ 4.5).

**12.4 Mobility in soil**

No information provided.

**12.5 Other adverse effects**

No information provided.

**13. DISPOSAL CONSIDERATIONS****13.1 Waste treatment methods**

**Waste disposal** For small amounts, mix with sand and dispose of to approved landfill. For larger quantities, dissolve in flammable solvent and incinerate at an approved facility equipped with after burner and scrubber.

**Legislation** Dispose of in accordance with relevant local legislation.

**14. TRANSPORT INFORMATION**

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE



	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
<b>14.1 UN Number</b>	1993	1993	1993
<b>14.2 Proper Shipping Name</b>	FLAMMABLE LIQUID, N.O.S. (contains ethyl acetate, hydrocarbons, c9-c11, n-alkanes, isoalkanes, cyclics, <2% aromatics)	FLAMMABLE LIQUID, N.O.S. (contains ethyl acetate, hydrocarbons, c9-c11, n-alkanes, isoalkanes, cyclics, <2% aromatics)	FLAMMABLE LIQUID, N.O.S. (contains ethyl acetate, hydrocarbons, c9-c11, n-alkanes, isoalkanes, cyclics, <2% aromatics)
<b>14.3 Transport hazard class</b>	3	3	3
<b>14.4 Packing Group</b>	II	II	II

**14.5 Environmental hazards**

No information provided.

**14.6 Special precautions for user**

**Hazchem code** ●3YE  
**GTEPG** 3A1  
**EmS** F-E, S-E

**15. REGULATORY INFORMATION****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

**Poison schedule** A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

**Classifications** Safe Work Australia criteria is based on the Globally Harmonised System (GHS) of Classification and Labelling of Chemicals (GHS Revision 7).

**Inventory listings** **AUSTRALIA: AIIC (Australian Inventory of Industrial Chemicals)**  
 All components are listed on AIIC, or are exempt.

**16. OTHER INFORMATION**

## PRODUCT NAME **AGER**

### Additional information

**WORK PRACTICES - SOLVENTS:** Organic solvents may present both a health and flammability hazard. It is recommended that engineering controls should be adopted to reduce exposure where practicable (for example, if using indoors, ensure explosion proof extraction ventilation is available). Flammable or combustible liquids with explosive limits have the potential for ignition from static discharge. Refer to AS 1020 (The control of undesirable static electricity) and AS 1940 (The storage and handling of flammable and combustible liquids) for control procedures.

**EXPOSURE STANDARDS - TIME WEIGHTED AVERAGES:** Exposure standards are established on the premise of an 8 hour work period of normal intensity, under normal climatic conditions and where a 16 hour break between shifts exists to enable the body to eliminate absorbed contaminants. In the following circumstances, exposure standards must be reduced: Strenuous work conditions; hot, humid climates; high altitude conditions; extended shifts (which increase the exposure period and shorten the period of recuperation).

**WORKPLACE CONTROLS AND PRACTICES:** Unless a less toxic chemical can be substituted for a hazardous substance, **ENGINEERING CONTROLS** are the most effective way of reducing exposure. The best protection is to enclose operations and/or provide local exhaust ventilation at the site of chemical release. Isolating operations can also reduce exposure. Using respirators or protective equipment is less effective than the controls mentioned above, but is sometimes necessary.

#### PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as form of product, method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

#### HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: form of product; frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

### Abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists
CAS #	Chemical Abstract Service number - used to uniquely identify chemical compounds
CNS	Central Nervous System
EC No.	EC No - European Community Number
EMS	Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous Goods)
GHS	Globally Harmonized System
GTEPG	Group Text Emergency Procedure Guide
IARC	International Agency for Research on Cancer
LC50	Lethal Concentration, 50% / Median Lethal Concentration
LD50	Lethal Dose, 50% / Median Lethal Dose
mg/m <sup>3</sup>	Milligrams per Cubic Metre
OEL	Occupational Exposure Limit
pH	relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).
ppm	Parts Per Million
STEL	Short-Term Exposure Limit
STOT-RE	Specific target organ toxicity (repeated exposure)
STOT-SE	Specific target organ toxicity (single exposure)
SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons
SWA	Safe Work Australia
TLV	Threshold Limit Value
TWA	Time Weighted Average

**PRODUCT NAME    AGER**

**Report status**

This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

**Prepared by**

Risk Management Technologies  
5 Ventnor Ave, West Perth  
Western Australia 6005  
Phone: +61 8 9322 1711  
Fax: +61 8 9322 1794  
Email: [info@rmt.com.au](mailto:info@rmt.com.au)  
Web: [www.rmtglobal.com](http://www.rmtglobal.com)

**[ End of SDS ]**